



## QUALITY CERTIFICATE – SMOR 3ZN HT15-158-8 50M (7,6)

JSM CODE: 4FF25151583401

### STIFF STAY KNOT



| Spaces between horizontal wire |
|--------------------------------|
| 15,24cm                        |
| 15,24cm                        |
| 15,24cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |
| 10,16cm                        |

| DIMENSION         |                 |                         |            |
|-------------------|-----------------|-------------------------|------------|
| Height            | Length          | Space between stay wire | Line wires |
| 1.58m (+/- 0.01m) | 50m (+/- 0.76m) | 7,62cm (+/-)            | 15         |

| TECNICAL INFORMATION |                      |                  |                                  |
|----------------------|----------------------|------------------|----------------------------------|
| Wires                | Diameters            | Tensile Strength | Galvanisation                    |
| Line                 | 2.50mm (+/- 0.060mm) | 1200/1400MPa     | 245grs/m <sup>2</sup> (minimum)  |
| Stay                 | 2.50mm (+/- 0.060mm) | 700/900MPa       | 245grs/m <sup>2</sup> ( minimum) |
| Knott                | 2.50mm (+/- 0.060mm) | 400/550MPa       | 245grs/m <sup>2</sup> ( minimum) |

Quality Department  
Catarina Moreira