

# FINISH NAILER



**IM65 F16** PRODUCT CODE: 013323

The **IM65** is a compact, quick and durable straight finish nailer with a no-mar tip to enable precise fixing.

## IDEAL USERS

Carpenter or Joiner working on both New Build and Renovation projects.



### FEATURE

- 30 Joules of power
- Lightest and best-balanced finish nailer
- Fast charging, high performing Lithium battery (200 shots in just 2 minutes)
- Optimised nose design and clear line of sight



### BENEFIT

- Ideal power ensures a flush finish in all soft woods and dense MDF
- Allows user to manoeuvre into tight spaces and work fatigue-free
- Delivers up to 10,000 shots per charge, equates to 5 brad fuel packs
- Provides easy access in the event of a jam



## CONSUMABLES

- Wide range of F16 brads available in ELECTRO GALV and STAINLESS STEEL
- IM65 Straight F16 brads available in sizes 16 - 63mm
- Short brad kit is available in each tool case to fix brads between 16 - 25mm

## DID YOU KNOW:

- 1 lithium battery is compatible for 7 Paslode tools. Product Code: 018880

# FINISH NAILER



**IM65A F16** PRODUCT CODE: 013313

The **IM65A** is a compact, quick and durable angled finish nailer with a no-mar tip to enable precise fixing into tight spaces.

## IDEAL USERS

Carpenter or Joiner working on both New Build and Renovation projects.



### FEATURE

- 30 Joules of power
- Distinctive angled magazine
- Lightest and best-balanced finish nailer
- Fast charging, high performing Lithium battery (200 shots in just 2 minutes)
- Optimised nose design and clear line of sight



### BENEFIT

- Ideal power ensures a flush finish in all soft woods and dense MDF
- Designed specifically for precision when working in corners and tight spaces
- Allows user to manoeuvre into tight spaces and work fatigue-free
- Delivers up to 10,000 shots per charge, equates to 5 brad fuel packs
- Provides easy access in the event of a jam



## CONSUMABLES

- Wide range of F16 brads available in ELECTRO GALV and STAINLESS STEEL
- IM65A Angled F16 brads available in sizes 32 - 63mm

# FINE FINISH NAILER



**IM50 F18** PRODUCT CODE: 013333

The **IM50** finishing brad nailer is perfect for intricate detail applications, producing seamless fixes without the extra time of re-finishing work.

## IDEAL USERS

Carpenter or Joiner working on secret nailing applications such as cabinet and furniture work, beading and shop fitting.



### FEATURE

- 25 Joules of power
- Optimum line of sight and no mar tip
- Depth of drive adjustment
- Fast charging, high performing Lithium battery (200 shots in just 2 minutes)



### BENEFIT

- Ideal power ensures seamless fixes in all soft woods and dense MDF
- Enables user to increase accuracy in their fixings
- Guarantees a flawless finish
- Delivers up to 10,000 shots per charge, equates to 5 brad fuel packs



## CONSUMABLES

- Thinner 18 gauge brad for discreet fine finish nailing
- F18 straight brads available in sizes 16 - 50mm
- 1.2mm diameter brad available in ELECTRO GALV

## DID YOU KNOW:

- The IM50 tool is perfect when you need a **SUPER CLEAN** 2nd fix finish

# BRAD SELECTION GUIDES

## IM65 F16 BRADS

NAIL	FUEL CELLS	QTY	CODE	APPLICATIONS						
				Dado rail	Architrave	Skirting	Beading	Door stop	MDF fixing	Hardwood
F16 x 16mm	2	2000	921585							
F16 x 19mm	2	2000	921586							
F16 x 25mm	2	2000	921587							
F16 x 32mm	2	2000	921588							
F16 x 38mm	2	2000	921589							
F16 x 45mm	2	2000	921590							
F16 x 50mm	2	2000	921591							
F16 x 63mm	2	2000	921592							
F16 x 25mm	2	2000	921593							
F16 x 38mm	2	2000	921594							
F16 x 50mm	2	2000	921595							
F16 x 63mm	2	2000	921596							

## IM65A F16 BRADS

NAIL	FUEL CELLS	QTY	CODE	APPLICATIONS						
				Dado rail	Architrave	Skirting	Beading	Door stop	MDF fixing	Hardwood
F16 x 32mm	2	2000	300270							
F16 x 38mm	2	2000	300271							
F16 x 45mm	2	2000	300272							
F16 x 51mm	2	2000	300273							
F16 x 63mm	2	2000	300274							
F16 x 32mm	2	2000	300276							
F16 x 38mm	2	2000	300277							
F16 x 50mm	2	2000	300279							
F16 x 63mm	2	2000	300280							

## IM50 F18 BRADS

NAIL	FUEL CELLS	QTY	CODE	APPLICATIONS											
				Dado rail	Architrave	Skirting	Beading	Door stop	Stairs	Door set	Hand rail	Paneling	Cabinets	Palmetts	
F18 x 16mm	2	2000	395192												
F18 x 25mm	2	2000	395193												
F18 x 32mm	2	2000	395194												
F18 x 38mm	2	2000	395195												
F18 x 50mm	2	2000	395196												

- ELECTRO-GALV (INDOOR)
- STAINLESS STEEL A2-304 (OUTDOOR)



Paslode tools have a standard 2 year warranty, covering all components providing that Manufacturer's Operating Instructions have been followed, that no modifications have been made or non-original components or spare parts have been used, and that the tool has not been accidentally damaged or neglected.



www.paslode.co.uk

1 Wheatstone Place, Southfield Industrial Estate  
Glenrothes, Fife KY6 2SW



Customer Services:  
0800 833381



923595/4757/09.22

# POCKET GUIDE

QUICK GUIDE TO ALL PASLODE PRODUCTS

SCAN THE QR CODE



# FRAMING NAILER



CAPABLE OF FIRING NAIL SCREWS

## 360Xi

PRODUCT CODE: 019700

The 360Xi framing nailer is light and perfectly balanced to guarantee a great performance for multiple applications. A high performing lithium battery and a weatherproof fuel cell ensures the tool will run all day, every day no matter the challenge.

### IDEAL USERS

Carpenter, Roofer or General Builder working on New Build projects such as large housing developments.



#### FEATURE

- Unbeatable power to weight ratio, the most powerful Paslode framing nailer: 105 Joules
- Light and perfectly balanced with a re-engineered grip and new battery position
- Quick release magazine
- Fast charging, high performing Lithium battery (200 shots in just 2 minutes)
- Cold weather performance



#### BENEFIT

- Able to drive 90mm Ring Shank nails into the hardest substrates
- Ensures extra comfort and convenience with reduced fatigue, guaranteeing all day productivity
- Designed to eliminate nail jams
- Delivers up to 13,000 shots per charge, equates to over 5 nail fuel packs
- Allows user to work down to -15°C



#### CONSUMABLES

- Requires Paslode 2.8 or 3.1mm RoundDrive nails. Available in sizes from 51 - 90mm
- Smooth or Ring Shank nails are available

#### DID YOU KNOW:

The Paslode No-mar Cladding probe is available as an interchangeable accessory. Product Code: 019783

# FRAMING NAILER



NEW

## IM350+

PRODUCT CODE: 906500

The NEW and improved version of the iconic IM350+ tool heralds the seventh generation of Paslode gas nailing technology. Benefitting from 40 years of customer insight and innovation, the tool is strong and durable, guaranteeing tool performance and reliability.

### IDEAL USERS

Carpenter, Roofer or General Builder working on New Build and Renovation projects.



#### FEATURE

- Powerful Paslode framing nailer: 82 Joules
- Longer fan run time
- New rubberized grip for improved handling and feel
- Fast charging, high performing Lithium battery (200 shots in just 2 minutes)
- Bigger battery notch



#### BENEFIT

- Suitable for versatile framing applications
- Improved tool cooling with longer fan cycle for rapid firing
- Added comfort and control for improved ergonomics and manoeuvrability
- Delivers up to 9,000 shots per charge, equates to over 4 nail fuel packs
- Easier battery insertion and removal



#### CONSUMABLES

- 2.8 or 3.1mm clipped nail available in sizes from 50 - 90mm. Smooth or Ring Shank nails are available
- Wide range of Paslode Nail Fuel Packs available

#### DID YOU KNOW:

1 lithium battery is compatible for 7 Paslode tools. Product Code: 018880

# FRAMING NAILS

### EUROCODE 5 SERVICE CLASS

All Paslode framing nails are classified according to Eurocode 5 Service Class 1, 2 and 3 providing a suitable nail for every application

### CORROSION REQUIREMENTS OUTLINED IN EC5

Service Class 1 INDOORS	Service Class 2 INDOORS NOT HEATED, OUTDOORS PROTECTED	Service Class 3 OUTDOORS, EXPOSED TO WEATHER
BRIGHT		
ELECTRO GALV ≥ 12µm and GALV-PLUS® ≥ 15µm		
HOT DIPPED GALVANISED ≥ 55µm		
STAINLESS STEEL - A2 (AISI 304) & A4 (AISI 316)		

All Paslode nails are hexavalent chromium, cadmium and lead free. Technical documentation available via the website - [www.paslode.co.uk](http://www.paslode.co.uk)

### APPROVALS

- European safety standard EN ISO11148-13 outlines the safe operation of Paslode tools. Only those fuel cells and consumables identified in the operating manual should be used
- Paslode 3.1 x 63mm Galvanised Plus IM350+/360Xi Ring Shank nail will equal or better the performance of batten fixings outlined in the British Standards BS 5534



### NAIL SHANK TYPES

- RING SHANK:** Provides the highest withdrawal resistance. Fixing across the grain
- SMOOTH SHANK:** Offers high shear value and lowest withdrawal resistance. Fixing across the grain and into end grain

### NAILSCREW®

Revolutionary Paslode NailScrew® system which combines the speed of gas nailing with the simplicity of a screw. Six times faster than standard wood screws. Each box supplied with FREE TX bit. Available in sizes from 50 - 75mm

# NAIL SELECTION GUIDES

### 360Xi NAILS

NAIL	FUEL CELLS	QTY	CODE	Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding	Fencing
51 x 2.8mm Ring	3	3300	141083											
63 x 2.8mm Ring	3	3300	141078											
75 x 3.1mm Ring	2	2200	141081											
90 x 3.1mm Smooth	2	2200	141076											
90 x 3.1mm Ring	2	2200	141082											
50 x 2.8mm NailScrew*	1	1100	141084											
51 x 2.8mm Ring	3	3300	141075											
51 x 2.8mm Ring	1	1100	141080											
63 x 2.8mm Ring	3	3300	141071											
63 x 2.8mm Ring	1	1100	141079											
63 x 3.1mm Ring	2	2200	141073											
65 x 2.8mm NailScrew*	1	1100	141086											
75 x 2.8mm NailScrew*	1	1100	141085											
75 x 3.1mm Ring	2	2200	141072											
90 x 3.1mm Smooth	2	2200	141070											
90 x 3.1mm Smooth	1	1100	141077											
90 x 3.1mm Ring	2	2200	141074											
63 x 2.8mm Ring	3	3300	140631											
63 x 3.1mm Ring	2	2200	140625											
75 x 3.1mm Ring	2	2200	140630											
90 x 3.1mm Smooth	2	2200	140629											
90 x 3.1mm Ring	2	2200	140628											
50 x 2.8mm NailScrew A2	1	1100	140633											
51 x 2.8mm Ring A2	1	1100	140624											
63 x 2.8mm Ring A2	1	1100	140626											
63 x 2.8mm Ring A4	1	1100	140632											
80 x 3.1mm Ring A2	1	1100	140627											

\*ELECTRO GALV ≥ 12µm

### IM350+ NAILS

NAIL	FUEL CELLS	QTY	CODE	Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding	Fencing
51 x 2.8mm Ring	3	3300	141202											
63 x 2.8mm Ring	3	3300	141208											
75 x 3.1mm Ring	2	2200	141226											
90 x 3.1mm Smooth	2	2200	141233											
51 x 2.8mm Ring	3	3300	141204											
51 x 2.8mm Ring	1	1100	141256											
63 x 2.8mm Ring	3	3300	141210											
63 x 2.8mm Ring	1	1100	141259											
63 x 3.1mm Ring	2	2200	141221											
75 x 3.1mm Ring	2	2200	141227											
90 x 3.1mm Smooth	2	2200	141234											
50 x 2.5mm Ring	2	2200	141200											
51 x 2.8mm Ring	3	3300	141205											
63 x 2.8mm Ring	3	3300	141211											
63 x 3.1mm Ring	2	2200	141222											
75 x 3.1mm Ring	2	2200	141228											
75 x 3.1mm Ring	1	1100	141265											
90 x 3.1mm Smooth	2	2200	141235											
90 x 3.1mm Smooth	1	1100	141267											
90 x 3.1mm Unilock	2	2200	141236											
51 x 2.8mm Ring A2	1	1100	141257											
63 x 2.8mm Ring A2	1	1100	141261											
80 x 3.1mm Ring A2	1	1100	141266											

Black hardened full head nail for metal roofing applications

# SPECIALIST NAILER



## PPNXi

PRODUCT CODE: 019790

The PPNXi is the first positive placement nailer on the market, providing an efficient and safe way of installing hangers, brackets and straps. The innovative locator probe accurately delivers a hardened twist nail in the precise required location.

### IDEAL USERS

Carpenters and Roofers working on-site, on both New Build and Renovation projects, fixing metal work connectors into wood.



#### FEATURE

- 77 Joules of power
- X6 faster than hand nailing the same applications
- Nose probe self locates to allow pinpoint accuracy
- Quick release magazine
- Fast charging, high performing Lithium battery (200 shots in just 2 minutes)
- Cold weather performance



#### BENEFIT

- Power to drive Hardened Twist nails into hard wood
- Reduces fatigue and personal injuries from having to nail in awkward positions
- Difficult to reach areas can now be filled, improving accessibility and durability
- Designed to eliminate nail jams and maximise runtime for high volume operations
- Delivers up to 13,000 shots per charge, equates to over 5 nail fuel packs
- Allows user to work down to -15°C



#### CONSUMABLES

- ELECTRO GALV Hardened Twist nails available in 35 x 3.4mm size



### PPNXi NAILS

NAIL	FUEL CELLS	QTY	CODE	Joist hangers	Truss clips	Connector plates	Strapping	Sole brackets	Z-clips
35 x 3.4mm Twist	2	2500	141185						
35 x 3.4mm Twist	1	1250	141189						

# SPECIALIST NAILER



## IM45 GN

PRODUCT CODE: 018608

The IM45 GN is the first cordless coil nailer. Its diverse range of nails suits many applications such as metal roofing and cladding.

### IDEAL USERS

Metal Roofers working on residential and commercial projects. Also suitable for Carpenters working on cladding applications.



#### FEATURE

- 30 Joules of power
- Unique delivery system is in a class of its own
- Simple and versatile tool
- No-mar rubber tip delivers a perfect flush finish
- Optimised nose design and clear line of sight



#### BENEFIT

- Ideal power ensures clean flush finish
- Decreased force needed to drive nails as opposed to hand nailing
- Nail collation suits many applications
- Prevents surface damage to building materials
- Aids accurate fixing, even in tight spaces



#### CONSUMABLES

- High nail capacity per coil: 125 nails
- No debris nail collation gives a clean flush finish

### IM45 GN NAILS

NAIL	FUEL CELLS	QTY	CODE	Metal roof install	External cladding	Overboarding	Fencing	Shingles	Flashing	Packaging	Temporary signage	Composite tiles
35 x 2.5mm NailScrew*	1	1000	142205									
40 x 2.5mm NailScrew*	1	750	142206									
25 x 2.8mm Ring	1	1000	142200									
25 x 2.8mm Ring A2	1	1000	142201									
32 x 2.8mm Ring A2	1	1000	142202									
35 x 2.5mm Ring A2	1	1000	142207									

\*ELECTRO GALV ≥ 12µm