



CLINGCOVER



Clingcover is the perfect masking film for all your construction, renovation and decorating jobs. This premium film clings to almost any surface and is treated with a unique formula that not only attracts paint overspray and dust but also reduces flaking. Made to withstand multiple uses, Clingcover reduces mess and clean up time

AVAILABLE SIZES

4m x 50m (142001)

Weight: 1.80kg per pack



WATER
RESISTANT



PUNCTURE
RESISTANT



EASY TO CUT

FEATURES

- Excellent stretchability and cling performance.
- Strong puncture and tear resistance.
- Good load stability during transport and storage.
- Flexible and easy to apply by hand.
- Reliable performance under stress and handling.
- Resistant to moisture, dust, and contamination.
- Suitable for a wide range of packaging applications.

TYPICAL PROPERTIES

Property	Value	Test Method
Density	0.956 g/cm ³	ASTM D1505
Melt index (190 °C / 2.16 kg)	20 g/10 min	AST D1238
Heat Deflection Tem. (0.45 MPa)	64 °C	ISO 75-2/B
Peak Melting Temperature	133 °C	ASTM D3418
Tensile Stress at Yield	23 MPa	ASTM D638
Tensile Strain at Yield	14 MPa	ISO 527-2/1A/50
Tensile Strain at Break	>100 %	ISO 527-2/1A/50
Flexural Modulus	970 MPa	ISO 178
Environmental Stress Crack Resistance 50 °C, 10% Igepal	2 hr	ASTM D1693
Notched Izod Impact Strength	4.0 kJ/m ²	ISO 180/1A

INSTRUCTIONS

- Ensure the surface is clean, dry, and free from sharp edges.
- Pull the required length of film from the roll.
- Wrap evenly around the product with consistent tension.
- For individual items, ensure full coverage on all sides.

The information contained in this document is provided in good faith and is based on available sources as of its issuance date. The information is intended for guidance only and is provided "as is". Icon Protection EMEA Ltd makes no warranty or representation as to its accuracy or completeness and disclaims all warranties, express or implied, including (without limitation) the implied warranties of merchantability and fitness for a particular purpose. The user is solely responsible for determining the suitability of the product to a specific application. Icon Protection EMEA Ltd recommends the user to test the product on a small, inconspicuous area prior to installation, as performance may be influenced by surface conditions, environmental factors, duration of use, and other factors beyond Icon Protection EMEA Ltd's control. To the maximum extent permitted by law, in no event shall Icon Protection EMEA Ltd be liable for any loss, damage, or expense arising from or in any way connected with the handling, storage, use, application, removal, or disposal of the product or, for any special, indirect, incidental or consequential damages whatsoever, regardless of whether such potential damages are foreseeable or if user has been advised of such damages. Nothing in this disclaimer excludes or limits any liability that cannot be excluded or limited under applicable UK law.

© 2026 Icon Protection EMEA Limited. Product names and attributes are trademarks of Icon Protection EMEA Limited, where applicable.