

CLOTH TAPE



Polyethylene cloth adhesive tape for general use. Thanks to its adhesive strength, it is ideal for sealing, repairs of all kinds, and packaging. The product is coated with a synthetic rubber adhesive using solvent-free technology.

AVAILABLE SIZES

48mm x 50m (142017)

Weight: 0.42kg per roll



HIGH TACK



EASY TEAR

FEATURES

- Water-repellent and durable.
- Suitable for multiple surfaces.
- Hand tearable.
- Heavy duty.
- High tack.

STORAGE & HANDLING

This product should be stored in a dry environment, protected from direct sunlight and frost conditions. Storage temperature should be maintained as close as possible to room temperature. Before application, ensure that the surface is clean, dry, and free from oil, grease, and dust. If the product has been stored at temperatures below 10°C, it is recommended to allow it to return to room temperature (between 15°C and 25°C) prior to use.

TYPICAL PROPERTIES

Property	Value	Test Method
Backing	PE laminated synthetic cloth	
Adhesive	synthetic rubber	
Total thickness	170 µm ± 10 %	Internal 5006
Tensile strength	25,6 N/cm	ASTM D-3330
Elongation at break	12% ± 10%	ASTM D-3759
Adhesion to steel	min 5,9 N/cm	ASTM D-3330
Colour	Black	
Size	48mm x 50m	

INSTRUCTIONS

- For optimum performance, Cloth Tape should be used within 12 months of date of shipment.
- Tape works best when applied to a surface that is clean, dry, and free of grease, oil, or other contaminants.
- Press firmly over the entire bonded area to ensure full contact and optimum adhesion.
- For irregular or curved surfaces, apply gradual pressure to allow the tape to conform to the substrate.

The information contained in this document is provided in good faith and is based on available sources as of its issuance date. The information is intended for guidance only and is provided "as is". Icon Protection EMEA Ltd makes no warranty or representation as to its accuracy or completeness and disclaims all warranties, express or implied, including (without limitation) the implied warranties of merchantability and fitness for a particular purpose. The user is solely responsible for determining the suitability of the product to a specific application. Icon Protection EMEA Ltd recommends the user to test the product on a small, inconspicuous area prior to installation, as performance may be influenced by surface conditions, environmental factors, duration of use, and other factors beyond Icon Protection EMEA Ltd's control. To the maximum extent permitted by law, in no event shall Icon Protection EMEA Ltd be liable for any loss, damage, or expense arising from or in any way connected with the handling, storage, use, application, removal, or disposal of the product or, for any special, indirect, incidental or consequential damages whatsoever, regardless of whether such potential damages are foreseeable or if user has been advised of such damages. Nothing in this disclaimer excludes or limits any liability that cannot be excluded or limited under applicable UK law.

© 2026 Icon Protection EMEA Limited. Product names and attributes are trademarks of Icon Protection EMEA Limited, where applicable.