

DOOR PROTECTORS



Our door protection film is designed to safeguard doors and door frames from scratches, dust, dirt, paint splashes, and minor impacts during manufacturing, transportation, storage, and installation. Manufactured from high-quality polyethylene resin, the film combines excellent strength with flexibility, allowing it to conform easily to a wide range of door surfaces while providing reliable surface protection.

AVAILABLE SIZES

95cm x 2.2m (142002)

5 pack weight: 0.06kg per pack

95cm x 2.2m (142003)

25 pack weight: 1.64kg per pack



WATER
RESISTANT



PUNCTURE
RESISTANT



EASY TO CUT

FEATURES

- Excellent tensile strength and flexibility for easy application without tearing.
- High impact and puncture resistance to withstand handling during transport and installation.
- Easy to cut, apply, and remove after use.
- Suitable for wood, metal, laminate, composite, painted, and coated door surfaces.

TYPICAL PROPERTIES

Property	Value	Test Method
Density	0.956 g/cm ³	ASTM D1505
Melt index (190 °C / 2.16 kg)	20 g/10 min	AST D1238
Heat Deflection Tem. (0.45 MPa)	64 °C	ISO 75-2/B
Peak Melting Temperature	133 °C	ASTM D3418
Tensile Stress at Yield	23 MPa	ASTM D638
Tensile Strain at Yield	14 MPa	ISO 527-2/1A/50
Tensile Strain at Break	>100 %	ISO 527-2/1A/50
Flexural Modulus	970 MPa	ISO 178
Environmental Stress Crack Resistance 50 °C, 10% Igepal	2 hr	ASTM D1693
Notched Izod Impact Strength	4.0 kJ/m ²	ISO 180/1A

INSTRUCTIONS

- Ensure the door surface is clean, dry, and free from dust, oil, or moisture before application.
- Cut the protection film to the required size.
- Position the film at the top or one edge of the door.
- Apply the film gradually, smoothing it over the surface to avoid wrinkles or air pockets.
- Ensure the film fully covers the areas requiring protection.

The information contained in this document is provided in good faith and is based on available sources as of its issuance date. The information is intended for guidance only and is provided "as is". Icon Protection EMEA Ltd makes no warranty or representation as to its accuracy or completeness and disclaims all warranties, express or implied, including (without limitation) the implied warranties of merchantability and fitness for a particular purpose. The user is solely responsible for determining the suitability of the product to a specific application. Icon Protection EMEA Ltd recommends the user to test the product on a small, inconspicuous area prior to installation, as performance may be influenced by surface conditions, environmental factors, duration of use, and other factors beyond Icon Protection EMEA Ltd's control. To the maximum extent permitted by law, in no event shall Icon Protection EMEA Ltd be liable for any loss, damage, or expense arising from or in any way connected with the handling, storage, use, application, removal, or disposal of the product or, for any special, indirect, incidental or consequential damages whatsoever, regardless of whether such potential damages are foreseeable or if user has been advised of such damages. Nothing in this disclaimer excludes or limits any liability that cannot be excluded or limited under applicable UK law.

© 2026 Icon Protection EMEA Limited. Product names and attributes are trademarks of Icon Protection EMEA Limited, where applicable.