

RUBBLE SACKS XL 5 PACK



Our Rubble Sacks are manufactured from high-quality polyethylene to provide exceptional strength, flexibility, and durability for demanding waste collection and disposal applications. Designed to withstand the rigours of construction, renovation, landscaping, and general clean-up projects, these sacks offer reliable performance when handling heavy and bulky waste materials.

AVAILABLE SIZES

55cm x 88cm (142004)

Weight: 0.36kg per pack



DURABLE



HEAVY DUTY



PUNCTURE
RESISTANT



INDOOR &
OUTDOOR USE

FEATURES

- Heavy-duty polyethylene construction for superior strength and durability.
- Designed to handle heavy construction, renovation, and landscaping waste.
- High tear and puncture resistance for demanding applications.
- Excellent flexibility helps prevent splitting under heavy loads.
- Strong enough for both indoor and outdoor use.

TYPICAL PROPERTIES

Property	Value	Test Method
Density	0.918 g/cm ³	ASTM D1505
Melt index (190 °C / 2.16 kg)	2.8 g/10 min	AST D1238
Peak Melting Temperature	120 °C	ExxonMobil Method
Tensile Strengths at Yield	12 MPa	ASTM D638
Tensile Strengths at Break	14 MPa	ASTM D638
Elongation at Yield	20 %	ASTM D638
Elongation at Break	690 %	ASTM D638
Flexural Modulus – 1% Secant	310 MPa	ASTM D790
Durometer Hardness (Shore D, 15 sec)	47	ASTM D2240
Volume Resistivity	> 1.0 × 10 ¹⁶ ohm·cm	ASTM D257
Dielectric Constant (60HZ)	2.2	ASTM D150
Dissipation Factor (60HZ)	< 4E-4	ASTM D150

INSTRUCTIONS

- Fill with rubble, construction waste, garden waste, or other suitable materials.
- Distribute the contents evenly to maintain balance. Avoid overloading.
- Take care when disposing of sharp or pointed objects, as these may puncture the sack.
- Gather the top of the sack and tie securely using a knot or suitable fastener before moving or disposing of the contents.
- Lift using safe manual handling techniques. For heavy loads, use mechanical lifting equipment or seek assistance from another person.

The information contained in this document is provided in good faith and is based on available sources as of its issuance date. The information is intended for guidance only and is provided "as is". Icon Protection EMEA Ltd makes no warranty or representation as to its accuracy or completeness and disclaims all warranties, express or implied, including (without limitation) the implied warranties of merchantability and fitness for a particular purpose. The user is solely responsible for determining the suitability of the product to a specific application. Icon Protection EMEA Ltd recommends the user to test the product on a small, inconspicuous area prior to installation, as performance may be influenced by surface conditions, environmental factors, duration of use, and other factors beyond Icon Protection EMEA Ltd's control. To the maximum extent permitted by law, in no event shall Icon Protection EMEA Ltd be liable for any loss, damage, or expense arising from or in any way connected with the handling, storage, use, application, removal, or disposal of the product or, for any special, indirect, incidental or consequential damages whatsoever, regardless of whether such potential damages are foreseeable or if user has been advised of such damages. Nothing in this disclaimer excludes or limits any liability that cannot be excluded or limited under applicable UK law.

© 2026 Icon Protection EMEA Limited. Product names and attributes are trademarks of Icon Protection EMEA Limited, where applicable.