

X-BOARD® SEAM TAPE



Paper seam tape designed for joining all temporary covering products like Ram Board and X-Board. It guarantees a precise and reliable join that will last throughout your job.

AVAILABLE SIZES

48mm x 50m (142015)

Weight: 0.28kg per roll



HIGH TACK



STRONG

FEATURES

- High adhesion.
- Good holding power.
- Hand tearable.
- Good contact on cardboard.

STORAGE & HANDLING

This product should be stored in a dry environment, protected from direct sunlight and frost conditions. Storage temperature should be maintained as close as possible to room temperature. Before application, ensure that the surface is clean, dry, and free from oil, grease, and dust. If the product has been stored at temperatures below 10°C, it is recommended to allow it to return to room temperature (between 15°C and 25°C) prior to use.

TYPICAL PROPERTIES

Property	Value	Test Method
Backing	Saturated crepe paper	
Adhesive	Synthetic rubber	
Total weight	107 g/m ²	
Total thickness	120 µm	Internal
Tensile strength	75 N/cm	AFERA 5004/ PSTC 131
Elongation at break	3% +/- 10%	AFERA 5004/ PSTC 131
Adhesion to steel	11 N/cm	AFERA 5001/ PSTC 101
Colour	Brown	
Size	48mm x 50m	

INSTRUCTIONS

- For optimum performance, Seam Tape should be used within 12 months of date of shipment.
- Seam Tape works best when applied to a surface that is clean, dry, and free of grease, oil, or other contaminants.
- DO NOT apply directly to floor or finished surface.

The information contained in this document is provided in good faith and is based on available sources as of its issuance date. The information is intended for guidance only and is provided "as is". Icon Protection EMEA Ltd makes no warranty or representation as to its accuracy or completeness and disclaims all warranties, express or implied, including (without limitation) the implied warranties of merchantability and fitness for a particular purpose. The user is solely responsible for determining the suitability of the product to a specific application. Icon Protection EMEA Ltd recommends the user to test the product on a small, inconspicuous area prior to installation, as performance may be influenced by surface conditions, environmental factors, duration of use, and other factors beyond Icon Protection EMEA Ltd's control. To the maximum extent permitted by law, in no event shall Icon Protection EMEA Ltd be liable for any loss, damage, or expense arising from or in any way connected with the handling, storage, use, application, removal, or disposal of the product or, for any special, indirect, incidental or consequential damages whatsoever, regardless of whether such potential damages are foreseeable or if user has been advised of such damages. Nothing in this disclaimer excludes or limits any liability that cannot be excluded or limited under applicable UK law.

© 2026 Icon Protection EMEA Limited. Product names and attributes are trademarks of Icon Protection EMEA Limited, where applicable.