

PRODUCT INFORMATION

VAPOR-CURE® TAPE

Ram Board Vapor-Cure® Tape is engineered with our exclusive Vapor-Cure® technology. When used to join Ram Board seams, it prevents cure lines and promotes even finishes in curing floors. This breathable tape allows vapors and moisture to escape from concrete, glue down floors, stained floors, epoxy floors, refinished floors, VCT, and most other floor types.



BREATHABLE



FEATURES

- Exclusive Vapor-Cure[™] technology
- Prevents cure lines in concrete
- Prevents blotchy finishes in curing floors
- Allows vapors and moisture to escape
- 3" Easily covers Ram Board seams

APPLICATIONS

- Construction
- Drywall
- Remodeling
- Painting
- Industrial
- Temporary Protection



AVAILABLE SIZES

RBVCT 3-108 3" x 108' (7.62cm x 32.91m)

TECHNICAL DATA:

Adhesion to Steel: 21.2 oz/in
Tensile Strength at Break: 5.5 lbf/in
Elongation at Break: 18%
Total Tape Thickness: 5.5 mil

Porosity: 10.5 sec./100 cc air/6.45 cm²

HANDLING AND STORAGE

Store in clean, cool & dry environment.

SHELF LIFE

For the best performance, use this product within 18 months from date of manufacturing.

PACKING

Will be available in required widths and in 108 ft length, packed in corrugated boxes.

SAFETY

SDS sheets for Ram Board products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2021 Ram Board, Inc. Product names & attributes trademark of Ram Board, Inc. where applicable.

